

RIG T-896 MOBILE DESERT RIG

TECHNICAL OVERVIEW

Rating **Hook load Drilling depth** theoretical

1,000 HP

500.000 lbs. @ 10 Lines

10,000 ft

Year of construction 2015

MAST

Free standing Telescopic Type Height 115 ft

Static Hook Load 500,000 lbs

SUBSTRUCTURE

Type Single Trailer Height 25 ft 500,000 lbs Casing load Setback load 270,000 lbs.

DRAWWORKS

Type Horsepower rating Max. line pull

Drilling line diameter Auxiliary brake

E-1000-AC, Disc brake

1.000 HP

500,000 lbs with 10 lines

1-1/4"

Dynamic motor brake

TOP DRIVE

Type NOV TDS 10SH 250 Tons Capacity Torque 22,000 ft.lbs

ROTARY TABL

Type

Table opening

Kerui ZP-275 AC

27 1/2"

IRON ROUGHNECK

Type

NOV ST 80

DRIVE GROUP

Engine type Horsepower Rating Generator type Generator rating Voltage Control Unit

Caterpillar 3512B 1,470 HP SR-4B 1,050 KW 600 VAC

AC-VFD 04 x ABB ACS 800



MUD SYSTEM

Pump type Horsepower rating Standpipe pressure

Shale shaker

Shale shaker type Active mud system

Reserve mud svstem

Water Tanks

2 x Bomco F-1000 AC

2 x 1,000 HP 5,000 psi 2 No.s

Derrick Hyper pool 2-skidMounted, 100m3 2-skid Mounted, 150m3

2-skid mounted, 150m3

BOP EQUIPMENT

 $13^{5}/8$ " - 5,000 psi Annular

Single ram

Double ram 13 ⁵/₈" - 5,000 psi

CAMP EQUIPMENT

Full rig camp for 100 personnel

ADDITIONAL EQUIPMENT

Air conditioned Driller Cabin with pressurized system. MD Totco Instrumentation. Soft Torque Rotary System Anti-collision for monkey board **KEMS** CCTV Cameras