

T-858 1500 HP MOBILE DESERT RIG

TECHNICAL OVERVIEW

Rating 1,500 HP

Hook load
Drilling depth
theoretical

800.000 lbs @ 10 Lines

16,000 ft

Year of construction 2010 (refurbished)

MAST

Type NOV, Cantilever for triple

Height 147 ft

Static Hook load 800,000 lbs with 10 lines

SUBSTRUCTURE

Type NOV Self elevating on wheels

 Height
 30 ft

 Casing load
 800,000 lbs

 Setback load
 450,000 lbs

DRAWWORKS

Type National, Model-110 EU

Horsepower rating 1,500 HP

Max. Hoisting load 710,000 lbs with 10 lines

Drilling line diameter 1-3/8"

Auxiliary brake Eddy Current, Type- 6032

TOP DRIVE

Type Varco TDS 9SA
Capacity 400 Ton
Torque 32,500 ft.lbs

ROTARY TABLE

Type National, C- 375

Table opening 37-½"

IRON ROUGHNECK

Type N/A

DRIVE GROUP

Engine type Horsepower Rating Generator type Generator rating Voltage Control Unit Caterpillar 3512 B 4 x 1436 HP AP-90-C6 Brushless 4 x 1200 KVA 600 V, 60 Hz SCR



MUD SYSTEM

Pump type 3 x National 10P-130
Horsepower rating 3 x 1,300 HP
Standpipe pressure 5,000 psi

Shale shaker 2 No.s

Shale shaker type Derrick flow line

 Active mud system
 962 bbl.
 153 m3

 Reserve mud syst.
 912 bbl.
 145 m3

 Water Tanks
 912 bbl.
 145 m3

BOP EQUIPMENT

Annular $13^{5}/_{8}$ " - 5,000 psi

Single ram NA

Double ram $13^{5}/_{8}$ " - 5000 psi

CAMP EQUIPMENT

Full rig camp for 100 men

ADDITIONAL EQUIPMENT

Rig can move with standing mast Anti-Collision System CCTV Camera KEMS